



STEAM GENERATORS

SG-08/SG-10

PRESSURE

4,5÷6
bar

STEAM FLOW RATE

75÷90
g/min

ABSORBED POWER

2÷3,2
kW

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTIBUG
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY



SG-08



SG-10
BOILER WITH AUTO FILLING TANK

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION



STAINLESS STEEL STRUCTURE SUITABLE FOR AREAS WHERE HYGENE IS A MUST



DIGITAL INDICATOR OF:
- BOILER TEMPERATURE
- STEAM READY
- WATER LACK

TECHNICAL DATA

		SG-8 S 4507 M	SG-10 S 5007 M	SG-10 S 6008 M
Code		GNVA40036	GNVA40037	GNVA40038
PERFORMANCE				
Operating pressure	bar/Mpa	4,5/0,45	5/05	6/0,6
Steam flow rate	g/min	~ 60-75	~ 65-80	~ 70-90
Max steam temperature	°C	150	155	160
Start up time	min	~ 9	~ 3	~ 2,5
Power supply	Ph-V-Hz	1-230/240-50/60	1-230/240-50/60	1-230/240-50/60
Max absorbed power	kW	2	2,2	3,2
Boiler volume	l	2	1,8 (continuous recharge)	1,8 (continuous recharge)
Water tank	l	-	2,5	2,5
Dimension (LxWxH)	cm	50x28x32	50x28x32	50x28x32
Weight	kg	6,5	7	8

STANDARD EQUIPMENT

CODE: IPIP40019
HANDGRIP + STEAM HOSE
2,5 m



CODE: MPVR40851
EXTENSION TUBE
L=500MM (2 PCS)



CODE: MPVR40852
NOZZLE JOINT



CODE: SPPV40052
GLASS CLEANER



CODE: SPPV40053
MULTIPURPOSE BRUSH



CODE: SPPV40054
TRIANGULAR BRUSH



CODE: SPPV40055
STEAM LANCE CURVED
L= 175



CODE: SPPV40056
SMALL ROUND BRUSH WITH
POLYESTER BRISTLES D.28



CODE: SPPV40057
SMALL ROUND BRUSH
WITH BRASS BRISTLES D.28



CODE: SPPV40058
RECTANGULAR CLOTH



OPTIONAL ACCESSORIES

CODE: MPVR40857
SELF REFFILING BOTTLE



CODE: AZMC40024
WRENCH FOR
MAINTENANCE



CODE: KTRI40446
TROLLEY





STEAM GENERATORS

SG-20/SG-30

PRESSURE

5 ÷ 5,5
bar

STEAM FLOW RATE

80 ÷ 100
g/min

ABSORBED POWER

3
kW



SG-20

SG-30 - BOILER WITH AUTO-FILLING TANK

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ SUCTION POWER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ LONG LIFE

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION.



CONTROL PANEL ENSURING A CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROLLER

TECHNICAL DATA

		SG-20 S 5008 M	SG-30 S 5510 M
Code		GNVA40016	GNVA40017
PERFORMANCE			
Operating pressure	bar/Mpa	5/0,5	5,5/0,55
Steam flow rate	g/min	0-80	0-100
Max steam temperature	°C	140	140
Start up time	min	~ 7	~ 7
Power supply	Ph-V-Hz	1-230-50	1-230-50
Max absorbed power	kW	3	3
Boiler volume	l	2,2	2,2 (auto-filling)
Water tank	l	2	2
Dimension (LxWxH)	cm	57x40x65	57x40x65
Weight	kg	11,5	12

STANDARD EQUIPMENT

CODE: IPIP45757
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(FOR SG-20)



CODE: IPIP40001
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(FOR SG-30)



CODE: KTRI46482
ACCESSORIES KIT
STEAM/SUCTION



OPTIONAL ACCESSORIES

CODE: IPIP47898
HANDGRIP + HOSE
STEAM 2,5 m
(FOR SG-20)



CODE: IPIP45815
HANDGRIP + HOSE
STEAM 5 m
(FOR SG-30)



CODE: KTRI40275
STEAM ONLY
ACCESSORIES KIT



CODE: KTRI89496
TROLLEY



CODE: KTRI40269
DESCALING KIT
(10 PHIALS)





STEAM GENERATORS

SG-20/SG-30

PRESSURE

5,0-5,5
bar

FLOW RATE

80-100
g/min

ABSORBED POWER

3,0
kW



SG-20

SG-30 - BOILER WITH AUTO-FILLING TANK

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ SUCTION POWER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ LONG LIFE

MOST FREQUENTLY USE

AUTOMOTIVE

HO.RE.CA.


FOOD INDUSTRY AND RETAILERS

LARGE COMMON AREAS

SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION.



CONTROL PANEL ENSURING A CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROLLER

TECHNICAL DATA

		SG-20 S 5008 M	SG-30 S 5510 M
Code		GNVA40016	GNVA40017
PERFORMANCE			
Operating pressure	bar/Mpa	5/0,5	5,5/0,55
Steam flow rate	g/min	0-80	0-100
Max steam temperature	°C	140	140
Start up time	min	~ 7	~ 7
Power supply	Ph-V-Hz	1-230-50	1-230-50
Max absorbed power	kW	3	3
Boiler volume	l	2,2	2,2 (auto-filling)
Water tank	l	2	2
Dimension (LxWxH)	cm	57x40x65	57x40x65
Weight	kg	11,5	12

STANDARD EQUIPMENT

CODE: IPIP45757
**HANDGRIP + HOSE
 STEAM/SUCTION MT 2,5
 (FOR SG-20)**



CODE: IPIP40001
**HANDGRIP + HOSE
 STEAM/SUCTION MT 2,5
 (FOR SG-30)**



CODE: KTRI40277
**ACCESSORIES KIT
 STEAM/SUCTION**



OPTIONAL ACCESSORIES

CODE: IPIP47898
**HANDGRIP + HOSE
 STEAM 2,5MT
 (OPTIONAL FOR SG-20)**



CODE: IPIP45815
**HANDGRIP + HOSE
 STEAM 5MT
 (OPTIONAL FOR SG-30)**



CODE: KTRI40275
**STEAM ONLY
 ACCESSORIES KIT**



CODE: KTRI89496
TROLLEY



CODE: KTRI40269
**DESCALING KIT
 (10 PHIALS)**





STEAM GENERATORS

SG-48 S 8010M

PRESSURE

8
bar

STEAM FLOW RATE

100
g/min

ABSORBED POWER

3,4
kW



EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOIL
- ▶ ANTI BUGS
- ▶ POWER FILTER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ POWER FLEX
- ▶ LONG LIFE
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



DIGITAL INDICATOR OF: STEAM TEMPERATURE, STEAM READY AND LACK OF WATER.



STAINLESS STEEL STRUCTURE



5 LITRES DETERGENT AND WATER TANK

TECHNICAL DATA

		SG-48 8010 M
Code		GNVA40043
PERFORMANCE		
Operating pressure	bar/Mpa	8/0,8
Steam flow rate	g/min	100
Steam temperature (max)	°C	180
Start up time	min	~ 5
Power supply	Ph-V-Hz	1-230-50
Absorbed power max.	kW	3,4
Vacuum power	kW	1,2
Boiler volume	l	3,5
Water tank	l	5
Dimension (LxWxH)	cm	74x51x104
Weight	Kg	34

STANDARD EQUIPMENT

CODE: IPIP40012
HANDGRIP + HOSE 4 m



CODE: MPVR40958
HOSE EXTENSION
L=500 mm 2 PZ



CODE: SPPV40060
MULTIPURPOSE FLOOR
BRUSH



CODE: SPPV40061
CARPET PROTECTION FOR
MULTIPURPOSE BRUSH



CODE: SPPV40062
FRAME WITH BRISTLES AND
RUBBER SCRAPERS FOR
MULTIPURPOSE BRUSH



CODE: SPPV40063
GLASS CLEANER



CODE: SPPV40064
PROFESSIONAL
TRANSPARENT NOZZLE



CODE: SPPV40065
LARGE SUCTION NOZZLE
+ SQUEEGEE



CODE: SPPV40066
SMALL SUCTION NOZZLE



CODE: SPPV40067
STEAM LANCE



CODE: SPPV40056
ROUND BRUSH POLYESTER
BRISTLE Ø28 mm



CODE: SPPV40068
ROUND BRUSH POLYESTER
BRISTLE Ø65 mm



CODE: SPPV40069
ROUND BRUSH POLYESTER
BRISTLE Ø40 mm



CODE: SPPV40070
ROUND BRUSH INOX
BRISTLE Ø40 mm



CODE: AZMC40024
KEY FOR MAINTENANCE



CODE: SPPV40058
RECTANGULAR CLOTH

